## **NORD PL-US-OMRON MD**

Optimize your internal logistics bv automating the internal transportation of pallets with the Nord Modules US Pallet Lift top module.

The NORD US Pallet Lift autonomously picks up and delivers pallets in the Pallet Rack.

Stable handling and transport of pallets. It enables the OMRON MD-650 and MD-900 to lift pallets autonomously from the Pallet Rack and lowers the pallet for stable transportation of payloads up to 550 kg for MD-650 and 800 kg for MD-900.





| Designated use       | For autonomous pickup and unload of pallets and other lifting applications |  |
|----------------------|--|--|
| Robot compatibility  | Omron MD-650 & MD-900  |  |
| NORD compatibility   | NORD Pallet Rack MD & NORD P&D Cantilever Stand                            |  |
| Weight               | 100 kg   220 lbs   |  |
| Max payload capacity | 550 & 800 kg   1 212 & 1 763 lbs   |  |
| Disclaimer           | Specifications may vary based on local conditions and application          |  |



Zero to low maintenance 600.000+ lifts

**High industrial** level of quality Max payload of 550 & 800 kg

## Specifications



Lifting height



| Performance                            |                                    |
|--|------------------------------------|
| Number of lift cycles with max payload | Minimum 600 000                    |
| Lifting speed                          | Up: 4 s - Down: 4s                 |
| Data collection                        | Error codes + data transfer to AMR |
| Motion type                            | Servo technology                   |
| Function                               | Manual override buttons            |
| Emergency stops                        | Emergency stops at all 4 corners   |
|  |                                    |
| Dimensions                             |                                    |
| Length                                 | 1 187 mm   46.7 in                 |
| Width                                  | 944 mm   37.2 in                   |
| Height                                 | 105 mm 3.94 in                     |

| 80 mm   3.15 in |  |
|-----------------|--|
|                 |  |
|                 |  |

| Optional Add-ons               |  |
|--------------------------------|--|
| 1. Payload detection sensor    | Detects whether there is an object on the P&D Stand  |
| 2. Barcode system (QR scanner) | For scanning QR/barcode on goods at the gate         |
| 3. Payload measurement kit     | Weighing the load being transported                  |
| 4. Blue light signal interface | Connection available for attachement of a blue light |